



Environmental
Programs

OVERVIEW OF CAMP EDWARDS F&T MODELING ACTIVITIES FOR DEMOLITION AREA 1

Jay Clausen, Diane Curry, Tod Monks, Jacob Zaidel (AMEC)



Presented to NGB, USGS, USEPA, MADEP, USACE & Jacobs Eng.

on 8/28/01(IAGWSPO Contact Dave Hill, 508-968-5621).




HISTORICAL OVERVIEW

- Submitted Draft Model Selection Document - 07/22/99
- Submitted Final Model Selection Document - 05/16/00
- Modeling Summit w/AEC, WES, Jacobs, USGS, DEP, EPA - 09/19/00
- Submitted Draft Modeling Strategy Document - 03/26/01
- Modeling Meeting w/AEC, WES, Jacobs, USGS, DEP - 04/03/01
- Ongoing Modeling Meetings/Discussions w/USGS, WES, AEC, Jacobs



DEMO 1 LOCATION



LEGEND

- Soil Grid Samples
- Sediment Samples
- Groundwater Grab Samples
- Surface Water Samples
- Soil Boring Samples
- Groundwater Samples
- Cape Moraine



MAJOR SOURCES OF INFORMATION

- USGS Regional Model, Reports, and Discussions
- AMEC/OGDEN Reports
- Jacobs Engineering Group Inc. Reports
- JPO/Water-Supply Reports
- MMR Related Technical Papers and Articles



MODELING OBJECTIVES

- Primary Objectives
 - Develop Sub-Regional F&T Model(s) for Demo 1 Using MODFLOW and MT3D in GMS
 - Calibrate F&T Model to Present Steady-State Conditions for RDX
 - Predict F&T of RDX from (Past to Present) and (Present to Future, i.e. 30 years)
 - Identify Present Impacts on Groundwater Flow and Contaminant Transport Due to Water-Supply Wells



MODELING OBJECTIVES (cont.)

- Related Tasks
 - Conduct Sensitivity Analysis to Quantify the Uncertainty in Calibrated Model(s) Caused by Uncertainty in the Estimates of Aquifer Parameters and Transport Parameters
 - Utilize Model for Assessing Remedial Options
 - Utilize Model for Engineering Design
 - Document Demo 1 Modeling Approach, Results, and Conclusions



MODEL CODES

- MODFLOW (Flow)
- MT3D (Transport)





MODELING CHALLENGES

- Conversion From USGS Data Format to GMS Format Requirements
- Modifications of Regional USGS Model
- Development of Software Program to Facilitate Data Format Conversion From GMS to TECPLOT and GIS
- Transport Simulations (Three Models)
- Size of Subregional Model
 - Recompiled MODFLOW, MODPATH and MT3D Source Code
 - Upgrade of Computers
 - Development of FTP Site



MODELING PROCESS

**USGS REGIONAL
MODEL**

USGS REGIONAL
MODEL



AMEC REGIONAL
MODEL


USGS REGIONAL
MODEL





AMEC REGIONAL
MODEL





**USE MOD TMR FOR
SUBREGIONAL MODEL**






















SATURATED ZONE MODELING SITE CONCEPTUAL MODEL

- Hydrogeologic Setting
- Present Extent of Contamination






SPECIFICS OF DEMO 1

- Downgradient (west) of Groundwater Mound
- Horizontal Flow Gradients Predominate
- Relatively High Hydraulic Conductivity Zone
- Downgradient Extraction System (Bourne WS)
- Flow Direction and Gradients Insensitive to Seasonal Fluctuations in Precipitation and Aquifer Recharge



RDX PLUME MAP



- 0.25 - 2 ug/L
- 2 - 50 ug/L
- 50 - 100 ug/L
- > 100 ug/L



SUMMARY OF REGIONAL MODEL MODIFICATIONS

Regional Model	Modifications	Importance for Demo 1 Area
MMR-6	Increased K-Values in Southern Half of BBM	High
MMR-7	Updated Depth to Rock in Central Impact Area, Demo 1 and J Ranges	Low
MMR-8	Improved Representation of the Snake, Weeks, Wakeby and Mashpee Ponds	Low



REGIONAL MODEL




HYDRAULIC CONDUCTIVITY VALUES FOR DEMO 1 IN USGS MODEL

Model Layer	Elevation* (ft ngvd)	Range of K Values (ft/d)	K Values at Demo 1 (ft/d)
1	above 40	125 - 350	290
2	20 to 40	125 - 350	290
3	0 to 20	125 - 300	290
4	-20 to 0	100 - 290	290
5	-40 to -20	70 - 230	230
6	-60 to -40	70 - 230	230
7	-80 to -60	30 - 200	125
8	-100 to -80	10 - 125	70
9	-140 to -100	10 - 70	30
10	bedrock** to -140	10 - 70	30
11	NA	10 - 30	NA

*In the central portion; ** about -200 to -150 ft ngvd




DISTRIBUTION OF HYDRAULIC CONDUCTIVITY IN LAYER 1



(based on USGS Regional Model)



MEASURED 2000 WATER-LEVELS AND MODEL COMPUTED CONTOURS






COMPARISON OF GRADIENTS


Gradients	Measured (2000)	Model Predicted*
Across the Plume Area	0.10%	0.08%
From Demo 1 to MMR Boundary	0.21%	0.27%


* Calibrated to 1993 water levels




FLOW PATH PREDICTIONS BETWEEN ORIGINAL USGS AND MODIFIED AMEC MODELS










10 Years






20 Years









40 Years


0 0.25 0.5 1 1.5 2 2.5




45 Years



50 Years




55 Years



60 Years




DEMO 1 PARTICLE TRACKS






DEMO 1 PARTICLE TRACKS





MODEL PREDICTED PARTICLE PATHS VS CURRENT PLUME CONFIGURATION






DEVELOPMENT OF DEMO 1 SUB-REGIONAL MODELS

- Demo 1-4C - Fate-and-Transport Calibration
- Demo 1-4N - No Action Scenario Analysis
- Demo 1-4R - Aquifer Remediation Scenario Analysis




DEMO-1 SUB-REGIONAL MODELS






WATER-LEVEL CONTOUR COMPARISON BETWEEN REGIONAL AND SUB-REGIONAL FLOW MODELS





NUMERICAL GRID FOR SUB-REGIONAL “NO-ACTION” MODEL





SUMMARY OF EPA HELP MODEL RESULTS FOR DEMO 1 AREA

1. Run-off From the Slopes Constitutes About 12% - 17% of Total Precipitation;
2. Run-off Occurs Primarily in Winter and Spring Due to the Snow Melt and Rain During Frozen Soil Conditions;
3. Recharge Along the Slopes Was Predicted to Be Lower by 20% - 30% Compared With “No Run-off” Condition;
4. Recharge in the Depression Area Was Predicted to Be Increased by About 50% Due to the Surface Run-off From Slopes.



MAJOR F&T COMPONENTS

Component	Description	Effect on Solution	Expected Importance
Advection	Migration along flow path	Preserves concentration levels along flow paths	High
Dispersion	Spreading around center of mass	Smears concentration fronts	Low
Retardation	Sorption to solid phase	Slows front propagation	Medium
Degradation	Transformation into another chemical	Reduces concentration levels	Low
Leaching	Contaminant loading from unsaturated zone	Controls concentration levels in source area and total mass	High



TRANSPORT CALIBRATION TARGETS

- Total Mass of RDX in Aquifer
- Distribution of RDX Mass with Depth
- Width of RDX Plume
- Maximum Extent of RDX Plume
- Maximum Depth of RDX Plume
- Maximum RDX Concentration



TRANSPORT CALIBRATION SUMMARY

Parameter	Model Predicted	Observed/Estimated
Total Mass of Dissolved RDX (kg)	14	16
Width of RDX Plume (ft)	450	500
Length of RDX Plume (ft)	5,600	5,500
Depth of RDX Plume (ft bwt)	90	80
Maximum Concentration of RDX within Demo 1 (ug/L)	420	390



MAJOR CONCLUSION OF F&T DEMO 1 MODEL CALIBRATION

4. Calibration Suggests Source Release Started 20-30 Years Ago
5. RDX Sources Do Not Show Any Notable Sign of Depletion
6. Acceptable Calibration was Achieved Using the Reported Dispersivity Values (Garabedian et al., 1991), i.e. Longitudinal Dispersivity of 3 ft, Transverse Dispersivity of 0.06 ft and a Vertical Dispersivity of 0.005 ft




FLOW & TRANSPORT SIMULATIONS

- No Action Scenario
- Gradient Control - Single Extraction Well
- Gradient Control - Single Extraction Well with Discharge to Demo 1 Surface
- Plume Collapse - Five Extraction Wells
- Plume Collapse - Five Extraction Wells Discharge to Demo 1 Surface
- Plume Collapse - Five Extraction Wells with ReInjection
- Other Scenarios




RDX NO ACTION PROJECTION - 30 YEARS INTO FUTURE






RDX PLUME - 30 YEAR PREDICTION






GRADIENT CONTROL - SINGLE EXTRACTION WELL






One extraction well T = +5 years






One extraction well T = +10 years






One extraction well T = +15 years






One extraction well T = +20 years






One extraction well T = +25 years






One extraction well T = +30 years






PLUME COLLAPSE - EXTRACTION ONLY

- 5 extraction wells
- Total Flow Rate of 145 gpm
- 50 ft screens, variable depth






Five extraction wells T = +5 years






Five extraction wells T = +10 years






Five extraction wells T = +15 years






Five extraction wells T = +20 years






Five extraction wells T = +25 years






Five extraction wells T = +30 years





Total Mass of RDX in Aquifer




— Single Well Pumping at Toe of Plume (100 gpm) — Five Wells Pumping at 145 gpm



PLUME COLLAPSE - SURFACE DISCHARGE AT DEMO 1

- 5 extraction wells
- Total Flow Rate of 109 gpm
- 50 ft screens, variable depth




Discharge of
Extracted Water



PLUME COLLAPSE - 5 EXTRACTION WELLS (2 AT TOE OF PLUME)

- 5 extraction wells
- Total Flow Rate of 155 gpm
- 50 ft screens, variable depth





DELIVERABLES AND SCHEDULE

- Draft FS - 10/16/01
- Final FS - 12/31/01
- Remedy Selection Plan - 01/28/02
- RA/RD - ???



CONCLUSIONS/RECOMMENDATIONS

- Subregional Model Developed that Matches Major Plume Parameters and Configuration
- Model Suggests Source(s) are 20 to 30 Years Old
- Source(s) are Still Active and Not Exhausted
- Existing Plume can be Captured by a Single Well at 100 to 150 gpm
- Plume Collapse is Possible Using Additional Extraction Wells
- Recalibration of Model After Collection of O&M Data and Refinement of O&M Parameters